techbelt

Product Data Sheet

TL-30-RB

Thickness (mm) Weight (g/m2) PTFE Content (%) Colour	0.30 600 67 Red / Blu	Tensile Strength (N/5 cm) Temperature Resistance (°C) Permeation Resistance μg/cm²/minute e	2400 -150 / +260 0.0
	Cast Film	 Material Properties Extremes of heat and cold resistance: Minus -73°C to Chemical inertness: Affected only by a few rare substances at very high temperatures High Release from sticky materials 'Non-Stick' Easy cleaning (Nothing bonds permanently) Low friction co-efficient: 0.04 – 0.10; depending on lot Chemical corrosion and moisture resistance Mildew and fungus resistance Ultra-Violet, Infra-Red, Micro-Wave, Radio Frequentian Non Combustible – Self Extinguishing Low Thermal Expansion: <5% 	bad and surface speed
	E Cast Film	 Food Approval (USFDA) Lightweight and energy efficient for economical ope 	ration

Additional Information

TL-30-RB features multi-layer PTFE cast film laminated on both sides of PTFE / glass fabric with a uniform thickness

Availability: This material as available ex stock and can be supplied at any width from 3mm up to 1000mm wide.

FDA Compliant: Suitable for use in direct food contact applications under the applicable requirements of 21CFR 177.1550

Fabric Care: Do not fold or crease when handling and installing. The fabric can eventually discolour in sunlight (turns white), but otherwise is unaffected by biological or chemical agents, heat or cold within its temperature range, or by most areas of the electric magnetic spectrum.

The material can be converted to engineered product. Consult our Technical staff for further details. Also available chemically etched one side for proprietary adhesive bonding. Standard etch is silica based, sodium based etch is available on request

PTFE (Teflon®) begins to soften at 260°C, increasing wear rate. Somewhat above 300°C, fumes are given off and these should not be inhaled. COSHH data is available upon request. After contact wash hands thoroughly before handling or smoking tobacco.



Techbelt Level 0 - 1850 Mill Shaw Lodge Mills Simmonds Lane Halifax HX3 9ET



<u>+44 (0)1422 34</u>4453



